



Blinds CC

Perfect Sun Control

WOOD VENETIAN BLINDS

The Ventolite "Wood Venetian" blind is available in 25 and 50mm slat width. Ventolite's natural Wood Venetian blind will expand your creative horizons and open vast design and colour possibilities, and as a result will offer a rich, warm and radiating look and feel.

Due to the nature of the "Wood" blind the following needs to be accepted and regarded as the norm.

- 1. Irregularities in finish
- 2. Colour and shade variations
- 3. Warpages
- 4. Colours do vary between widths, batches and shipments

The following must be considered when selling this product:

- 1. Must not be sold as a "block-out" blind
- 2. Slat do not close fully – especially with long drops
- 3. Fading is to be expected – especially the side facing the sun
- 4. Cleats are recommended for use on blinds with long drops
- 5. Not recommended in moist areas
- 6. If blinds are recess fitted, then gaps are to be expected

General:

- 1. Cleats are available on request
- 2. Cut-outs – please provide detailed drawing
- 3. Alternating slat colours are available on request
- 4. All blinds are supplied with universal installation brackets

Surcharges: - See Price Lists

- 1. Cleats
- 2. Cut-outs
- 3. Alternating slat colours
- 4. Return ends for face fix applications

Finishes:

- 1. Colour co-ordinated steel head rail
- 2. Colour co-ordinated wood bottom rail
- 3. Colour co-ordinated wood pelmet
- 4. Colour co-ordinated lift, tilt cords and ladder lace
- 5. Colour co-ordinated wood tassels

Maximum recommended sizes

Maximum Recommended Width For 50mm	2400mm
Maximum Recommended Drop For 50mm	2600mm
Maximum Recommended Area For 50mm	3.6m ²
Maximum Recommended Width For 25mm	2000mm
Maximum Recommended Drop For 25mm	2600mm
Maximum Recommended Area For 25 mm	3.0m ²

Contact Details: Tel: 031 579 2670
 Fax: 031 579 2680
 Email: orders@ventolite.co.za
 Web: www.ventolite.co.za

Address: Ventolite Blinds CC
 Unit 19 Springriver Park
 48 Ebonyfield Avenue
 Springfield Park
 Durban

Stacking:

Stacking Heights - 25mm Only

	Height			
	1000mm	1500mm	2000mm	2600mm
Stack	169mm	227mm	285mm	355mm

Stacking Heights - 50mm Only

	Height			
	1000mm	1500mm	2000mm	2500mm
Stack	135mm	165mm	195mm	225mm

Minimum recess recommended for installation:

25mm Wood – 35mm

50mm Wood – 70mm

Operation

Raising

With slats fully open, draw the cords vertically downwards until the desired height is reached, then incline cords slightly upwards to lock in position,

Never raise with slats in closed position.

Lowering

Pull cords towards the centre of the blind to disengage the cord lock and release gently through the hand until drop required is reached. Lock cords as in raising.

Tilting

In each hand, hold the open ended cords and slowly pull in a downward direction on one of the cords, this will now tilt the angle of the slats. By pulling the other cord in a downward direction, the angle of the slats will now move in the reverse direction.

Cleaning:

Regular dusting

Wipe with a warm damp cloth

Can be treated by suitable "Woodoc" products

Contact Details: Tel: 031 579 2670
Fax: 031 579 2680
Email: orders@ventolite.co.za
Web: www.ventolite.co.za

Address: Ventolite Blinds CC
Unit 19 Springriver Park
48 Ebonyfield Avenue
Springfield Park
Durban