

## 35mm Aluminium Venetian Blinds

### Specifications

35mm Slat Width	35mm
35mm Slat Thickness	0.21
Width of Headrail For 35mm	35mm
Height of Headrail For 35mm	24mm
Width of "C" Type Bottomrail For 35mm	30mm
Height of "C" Type Bottomrail For 35mm	10mm
Maximum Recommended Width For 35mm	3000mm
Maximum Recommended Drop For 35mm	2600mm
Maximum Recommended Area For 35mm	4.5m <sup>2</sup>
Minimum Width For 35mm	400mm, Both Tilt and Lift Cord on One Side
Maximum Ladder Lace Spacing From End To First ladder	150mm
Maximum Ladder Lace Spacing Between Ladders	450mm
Bottomrail	High Tensile Vynil Coated Aluminium
Slat	High Tensile Vynil Coated Aluminium
Headrail	High Tensile Vynil Coated Aluminium
Cord Lock Mechanism	Moulded Plastic & Metal
Internal Components	Moulded Plastic
Tassel, Equalizer, Wand, End Caps & Tape Buttons	Moulded Plastic
Tilter Mechanism	Moulded Plastic
Fixing Brackets	Metal, Zinc Chromate Primed
Tilt Shaft	Steel "D" Shape
Cords	Colour Co-ordinated 1.4mm Polyester Yarn
Ladder Lace For 35mm	Colour Co-ordinated 30mm x 38mm x 2mm Polyester Yarn

### Approximate Stacking Heights – 35mm

	Height			
	1000mm	1500mm	2000mm	2500mm
Stack	65mm	75mm	85mm	95mm

**Contact Details:** Tel: 031 579 2670  
 Fax: 031 579 2680  
 Email: [orders@ventolite.co.za](mailto:orders@ventolite.co.za)  
 Web: [www.ventolite.co.za](http://www.ventolite.co.za)

**Address:** Ventolite Blinds CC  
 Unit 19 Springriver Park  
 48 Ebonyfield Avenue  
 Springfield Park  
 Durban