

ROLLER BLINDS

The Ventolite Roller Blind is designed with care and consideration for customer needs. The large variety of fabrics can be used in any room in a home or business environment – to compliment existing furnishings or purely to look good whilst providing privacy, and protection to your furnishings.

The Ventolite Roller Blind can be either subtle and unobtrusive or bold and beautiful.

The plain or lightly textured natural shades will filter the light. Other “Sleep Tight” fabrics which have a more dense coating will reduce light penetration. The “Blackout” ranges are dense enough to exclude light.

Roller Blinds are available either the “Abamatic” or “Koin” side operated system.

Whatever the fabric, Windovert regrettably cannot be held responsible for any colour differences – This is governed by the fabric manufacturers “acceptable” yarn colour variance and therefore no guarantee is ever given due to the dye batch variation from time to time.

Due to the nature of the “Roller Blind” blind the following needs to be accepted and regarded as the norm.

1. Colour and shade variations
2. Colours do vary between widths, batches and shipments

The following must also be considered when selling this product:

1. Must not be sold as a “block-out” blind
2. Must not be sold as a privacy blind
3. Fading is to be expected – especially the side facing the sun

General:

1. Various valance styles are available on request
2. Please specify if there will be more than one blind in an opening
3. All blinds are supplied with either top or face fix installation brackets – “Koin System”
4. All blinds are supplied with universal brackets – “Abamatic System”
5. If blinds are recess fitted, then gaps are to be expected
6. All blinds can either be manufactured as a reverse or normal roll


Surcharges: - See Price Lists

1. Various valance styles

Maximum Sizes

Maximum Recommended Width - 3000mm

Maximum Recommended Drop - 3000mm



This will depend on material selection

Maximum m² area: 3.6m²

Minimum recess recommended for installation: 50mm

Contact Details: Tel: 031 579 2670
Fax: 031 579 2680
Email: orders@ventolite.co.za
Web: www.ventolite.co.za

Address: Ventolite Blinds CC
Unit 19 Springriver Park
48 Ebonyfield Avenue
Springfield Park
Durban

Operating Instructions

The chain control will have a stopper near the gear control, and one near the bottom of the chain. To lower the blind, pull the chain until the stopper is almost at the gear unit, and the same applies when lifting. *Do not attempt to over pull and force the stopper into the gear unit as this will damage the blind.*

Blind Maintenance:

Clean by vacuuming or wiping with a clean damp cloth for "Blackout" materials

Contact Details: Tel: 031 579 2670
Fax: 031 579 2680
Email: orders@ventolite.co.za
Web: www.ventolite.co.za

Address: Ventolite Blinds CC
Unit 19 Springriver Park
48 Ebonyfield Avenue
Springfield Park
Durban