



Blinds CC

Perfect Sun Control

Roller Blind Specification – Koin System

Top Aluminium Installation Track

Shall be 47mm wide x 13mm deep and powder coated in colour white.
Track will be supplied complete with specified installation brackets

Top Aluminium Barrel

The top barrel shall be aluminium size 33mm in diameter and will be supplied complete with gearbox and idle end cap. These will be firmly attached to the barrel.

Aluminium Pelmet

Shall be 37mm high and powder coated in colour white.

Tolerances

The gap between fabric and the end bracket at the idle end will not exceed 4mm and the gap between the fabric and the end bracket at the control side will not exceed 13mm

Top Barrel & Track Components

End Brackets – White Powder Coated Steel
Installation Brackets - Electroplated Zinc Metal Top & Face Fix
Gearbox - Plastic & Nylon
Spline For Top Barrel - P.V.C.

Operating Chain

The beaded operating chain consists of nylon with "Hostaform" mouldings.

Bottom Weight

Round Aluminium in colour natural - 21mm diameter
Will be supplied complete with suitable round plastic end caps

Fabric

The fabric will be as selected.

Maximum Sizes

Maximum Recommended Width - 3000mm
Maximum Recommended Drop - 3000mm
Maximum Recommended Area - 3.6m²

This will depend on material selection

Contact Details: Tel: 031 579 2670
Fax: 031 579 2680
Email: orders@ventolite.co.za
Web: www.ventolite.co.za

Address: Ventolite Blinds CC
Unit 19 Springriver Park
48 Ebonyfield Avenue
Springfield Park
Durban