

WOVEN WOOD BLINDS

Ventolite "Woven Wood" blinds are available in either a "Roller" or "Roman" style finish. Only the finest materials have been selected in our range.

Yarn and wood used on these fabrics have been specially selected. The wood slats retain the grain texture and irregularities inherent in natural wood with the most contemporary colours for a truly unique window covering.

Due to the nature of the "Woven wood" blind the following needs to be accepted and regarded as the norm.

1. Irregularities in finish and stitching
2. Colour and shade variations
3. Warpages of both the wood sticks and reids
4. Colours do vary between widths, batches and shipments

The following must also be considered when selling this product:

1. Must not be sold as a "block-out" blind
2. Must not be sold as a privacy blind
3. Fading is to be expected – especially the side facing the sun
4. Slight variations in drop may occur
5. Not recommended in moist areas
6. Pleated heights on "Roman" style blinds will vary on blinds with different heights
7. "Roman" style blinds are not recommended for all "Woven Wood, Asia or Flatwood" ranges

General:

1. Cut-outs – please provide detailed drawing
2. Various valance styles are available on request
3. Cleats will be supplied as standard
4. Please specify if there will be more than one blind in an opening
5. Please request an updated sample from the factory if your client insists on the current colour finish
6. All blinds are supplied with universal installation brackets
7. If blinds are recess fitted, then gaps are to be expected

Surcharges: - See Price Lists

1. Various valance styles
2. Cut-outs
3. Roman style

Maximum recommended sizes:

Width – 2400mm
Drop - 3500mm

Maximum m² area:

7.2m²

Contact Details: Tel: 031 579 2670
Fax: 031 579 2680
Email: orders@ventolite.co.za
Web: www.ventolite.co.za

Address: Ventolite Blinds CC
Unit 19 Springriver Park
48 Ebonyfield Avenue
Springfield Park
Durban



Blinds CC

Perfect Sun Control

Valance Heights:

For blinds up to 2000mm high:
150mm
For blinds 2000-2800mm high:
200mm
For blinds 2800-3500mm high:
250mm

Minimum recess recommended for installation:

Without use of installation bracket – 50mm
With universal installation bracket – 80mm

Operation:

Raising

Draw the cords vertically downwards until the desired height is reached, then incline cords slightly outwards to lock cords in position.

Lowering

Pull cords towards the centre of the blind to disengage the cord lock and release gently through the hand until drop required is reached. Lock cords as in raising.

Both “Roman and Roll-Up” blinds have the same basic hardware and operating procedure. Cords, whether installed on the left or right side have the same locking mechanism.

Blind Maintenance:

Clean by vacuuming

Contact Details: Tel: 031 579 2670
Fax: 031 579 2680
Email: orders@ventolite.co.za
Web: www.ventolite.co.za

Address: Ventolite Blinds CC
Unit 19 Springriver Park
48 Ebonyfield Avenue
Springfield Park
Durban